



	8	ı	7 6	1	5	4	ı	3	ı	2	 I	1	
	P/N	MAXIMUM PRESSURE RATING	FEMALE THREAD	FITTING END	SUGGESTED VENDOR	SUGGESTED VENDOR P/N							
	DT10751-1 DT10751-3	15000 PSI	.305-32 NATIONAL FORM	MS33656E4 1/8" NPT	AVALCO	AV5007 AV5008							
D	51161616				OURCE CON		<u>AWING</u>						D
С	L 0.75 HEX - 1												С
->				TYP		_	1						≪ -
В		<u>1</u>	DT10751-X HIGH PRESSU (DT1075	'	ALE THREAD ONNECTION				FITTING E	IND			В
_						RELEASE							
	NOTES: 1) MATERIAL: STA 2) FINISH: N/A 3) TOLERANCES: 4) UNITS: INCHES 5) BREAK SHARP 6) IDENTIFICATIO 7) WEIGHT: N/A	NINLESS STEEL N/A UNLESS OTHERWISE NO EDGES: N/A N: IDENTIFY PER DART Q	OTED SI 044			2022 04 0	1	DESIGN DRAWN CHECKED MFG. APPR. APPROVED DE APPR. DATE 21.0		DRAWING NO. DT10751 TITLE SCHRADER COPYRIGHT THIS DOCUMENT IS PRIVATE AND CO. NOT TO BE USED FOR AMP PURPOS NOT TO BE USED FOR AMP PURPOS	AEROSPACE BURY, ONTARIO, CAI VALVE FITT © 2021 BY DART AEROSP, WIDENTIAL AND IS SUPPLIED ON THE EX- E OR COPIED OR COMMUNICATED TO AM EXPRINSISION FROM DART AEROSPACE IT	REV. A SHEET 3 OF 5 SCALE SINGS NTS ACE LTD PRESS CONDITION THAT IT IS YOTHER PERSON WITHOUT	A



